



SMALL INSULATION CRIMP



43374-0001



REF.
.470
(11.94)
PROGRESSION

SCALE: 2:1

NOTES:

1. SINGLE CRIMP TO #16 & #14 AWG WIRE WITH .031/(0.79) MAXIMUM INSULATION THICKNESS.
2. MATERIAL: .012/(0.30) THICK C26000 BRASS.
3. FINISH: HOT TIN DIP.
4. DIMENSIONS FOR REFERENCE ONLY.
5. NO PORTION OF ONE LOCK TANG BEAM SHALL TOUCH ANY PORTION OF THE OTHER LOCK TANG BEAM.
6. PRODUCT SPECIFICATION: PS-43374-001

ADD BLOCK TOLERANCE EC NO: UCP2010-1826 DRW:NAELHAG 2010/02/08 CHKD:BWIRKUS 2010/02/09 APPR:FSMLTH 2010/02/10	DESCRIPTION REV	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
		▽=0	mm INCH	IN/MM	1:1	INCH	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION
		▽=0	4 PLACES ± --- ± ---	DRAWN BY DATE	TITLE		
		▽=0	3 PLACES ± --- ± .010	MAB 05/08/94	TERMINAL, RECEPTACLE .125/(3.18)X.020/(0.51) FLAT BLADE SYSTEM - TPA		
		2 PLACES ± 0.25 ± .014	CHECKED BY DATE	MOLEX MOLEX INCORPORATED DOCUMENT NO. SD-43374-0001 SHEET NO. 1 OF 1			
		1 PLACE ± 0.35 ± ---	KBP 05/08/94				
		ANGULAR ±1/2°	APPROVED BY DATE				
			RAS 05/08/94				
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	MATERIAL NO.				
			43374-0001				